

## Catalytic acetalization of glycerol for the production of 1,3-dioxolane as a platform chemical

박진서, 이정호, 이정양, 이지혜, 유주현, 김지만<sup>†</sup>

성균관대학교

(jimankim@skku.edu<sup>†</sup>)

Biodiesel has gained a considerable attention in recent years. The production of biodiesel involves a transesterification of vegetable oils to afford biodiesel and glycerol. Glycerol can be transformed into diverse derivatives. Among them, acetalization of glycerol has been reported to yield five and six membered acetal. In this research, glycerol conversion with acetone has been studied using mesoporous WO<sub>3</sub>/rod-type SBA-15 (WO<sub>3</sub>/R-SBA-15) as a catalyst. A series of catalysts with varying WO<sub>3</sub> loadings (5~20 wt%) were prepared by incipient wetness impregnation method. The catalysts were characterized with XRD, Raman spectroscopy, SEM, N<sub>2</sub> sorption analysis, and NH<sub>3</sub>-TPD. In the catalytic experiment, 10 wt% WO<sub>3</sub>/R-SBA-15 was found to be the most active catalyst. The catalyst exhibited 97% conversion with 97% selectivity for the five-membered cyclic product. Although the catalytic performance decreased in the 5<sup>th</sup> catalytic run, the catalyst was regenerated by calcination in 6<sup>th</sup> catalytic run. The excellent performance of the catalyst is mainly due to their high specific surface area and strong surface acid property.