

**Ordered mesoporous TiO<sub>2</sub> / SnO<sub>2</sub> was synthesized and characterized to improve the passability of current.**

최성립, 이정양, 김지만<sup>†</sup>

성균관대학교

(jimankim@skku.edu<sup>†</sup>)

In this study, we have successful synthesized ordered mesoporous SnO<sub>2</sub>/TiO<sub>2</sub> with three-dimensional bicontinuous cubic structure, high surface area and crystalline frameworks by using a facile solvent-free infiltration method from a mesoporous silica template of KIT-6 and employed as electrode in dye-sensitized solar cells. On the basis of the investigation of the XRD pattern, nitrogen adsorption (BET), dye adsorption, UV-vis diffuse reflectance spectroscopy, dark current, current-voltage(I-V) characteristics and electrochemical impedance spectra(EIS), it was found that when the Ti-content is 20wt%, the energy-conversion efficiency meso-SnO<sub>2</sub>/TiO<sub>2</sub> is significantly best, by about 1.95%. And it is mainly the result of TiO<sub>2</sub> particles on mesoporous SnO<sub>2</sub> electrode inhibited electron recombination caused by passivation of reactive surface states and increased the light scattering, leading to greatly improvement in the open-circuit voltage, short-circuit current, and fill factor.